

Kreisregner Kofler K-16

Düse Ø mm	Druck Atü	Wurfweite max. Mtr.	Leistung L/Min	Fläche mq.	mm/Std.
3.5	1.5	9.8	9.9	301	1.9
	2	10.6	11.4	353	1.9
	3	11.3	14	401	2.1
	4	12.2	16.2	467	2.1
	5	13	18.1	531	2
3.7	1.5	9.9	11.1	308	2.1
	2	10.9	12.8	373	2.1
	3	11.8	15.7	437	2.2
	4	12.6	18.1	498	2.2
	5	13.2	20.2	547	2.2
4	1.5	10	13	314	2.5
	2	11.2	14.9	394	2.3
	3	12.6	18.3	498	2.2
	4	13.5	21.1	572	2.2
	5	14.2	23.6	633	2.2
4.2	1.5	10.5	14.3	346	2.5
	2	11.7	16.5	430	2.3
	3	13	20.2	531	2.3
	4	14	23.3	615	2.3
	5	14.7	26	678	2.3
4.5	1.5	11.2	16.4	394	2.5
	2	12	18.9	452	2.5
	3	13.5	23.2	572	2.4
	4	14.5	26.7	660	2.4
	5	15	29.8	796	2.5
4.8	1.5	12.2	17.9	467	2.3
	2	13.1	20.6	539	2.3
	3	13.1	20.6	539	2.3
	4	15	29.1	706	2.5
	5	15.5	32.6	754	2.6